

CONT. BACKER ROD AND  
SEALANT (NOT BY  
LUDOWICI)

SILL FLASHING  
(NOT BY LUDOWICI)  
FLASHING SHOULD EXTENDN  
DOWN A MINIMUM OF 3" BELOW  
TOP OF TILE TO CONCEAL  
FASTENERS

SELF-ADHERED  
MEMBRANE  
(NOT BY LUDOWICI)

SEALANT OR TAPE AT  
RIGID INSULATION BOARD  
(NOT BY LUDOWICI)

FLEXIBLE SELF-  
ADHERING FLASHING  
(NOT BY LUDOWICI)

(2) STAINLESS STEEL  
FASTENERS PER TILE  
(TYP.)

AIR AND MOISTURE  
BARRIER (NOT BY  
LUDOWICI)

3/16" LUDOWICI  
DRAINAGE PLANE  
MATERIAL (NOT BY  
LUDOWICI)

LUDOWICI NEXCLAD  
SHINGLE 14 TERRACOTTA  
CLADDING TILE

WINDOW UNIT (NOT BY  
LUDOWICI)

EXTERIOR WALL FRAMING  
(NOT BY LUDOWICI)

CONTINUOUS RIGID STRUCTURAL  
INSULATION BOARD  
(NOT BY LUDOWICI)

2 1/8" NOM. EXTERIOR WALL CONSTRUCTION  
SYSTEM DEPTH (NOT BY LUDOWICI)



4757 Tile Plant Road  
New Lexington, Ohio 43764  
Telephone: (800) 945-8453 Fax: (740) 342-0025  
www.ludowici.com

SYSTEM: NeXclad Shingle 14

DETAIL #: 14rb

Description: WINDOW SILL SECTION W/CONTINUOUS RIGID  
STRUCTURAL INSULATION BOARD

Building Construction: Continuous Rigid Structural Insulation Board

Drawing Date: 2023.08.25

Scale: 3" = 1'-0"

Ludowici Reference #: NeXclad Shingle 14 14rb Designer

The information contained on this drawing is the property of Ludowici Roof Tile. Any use or reproduction in whole or in part without the express written permission of Ludowici Roof Tile is strictly prohibited.  
Ludowici Roof Tile, Inc. reserves the right to modify the configuration of item(s) shown without prior written notice.