



GENERAL NOTES:

- 1. THIS IS A PROTOTYPICAL DETAIL FOR REVIEW. MODIFICATIONS MAYBE REQUIRED TO MEET PROJECT SPECIFIC REQUIREMENTS.
- 2. A BEAD OF SEALANT SHOULD BE APPLIED BETWEEN THE LAP OF EACH HIP TILE.
- 3. TO MAINTAIN BOND LINES IN THE FIELD, THE FIRST FIELD TILE ADJACENT TO BONNET MAY NEED TO BE TRIMMED DOWN IN WIDTH.
- 4. IF JOINTS BETWEEN BONNETS AND FIELD TILES ARE LESS THAN 2" FROM UNDERLYING JOINTS, APPLY A 6" WIDE COPPER STEP FLASHING UNDER JOINT BETWEEN BONNET HIP ROLL AND FIELD TILE.
- 5. BONNET HIPS REQUIRE THE ROOF SLOPE OF THE INTERSECTING ROOF PLANES TO BE IDENTICAL.



4757 Tile Plant Road, P.O. BOX 69, New Lexington, OH 43764 Telephone: (888) 582-9052 Fax: (740) 342-1906 www.ludowici.com

SYSTEM:	Cottage Tile
Detail #:	COTTAGE-202
Description:	SECTION AT BONNET HIP
Drawing Date:	2014.10.11
Scale:	1-1/2" = 1'-0"
Ludowici N.A. Reference #:	Cottage Tile COTTAGE-202

The information contained on this drawing is the sole property of Ludowici Roof Tile, Inc. Any reproduction in whole or part without the express written permission of Ludowici Roof Tile, Inc. is strictly prohibited. Ludowici Roof Tile, Inc. reserves the right to modify the configuration of item(s) shown without prior written notice when deem necessary for product development and/or enhancement.