



**SECTION AT ROUNDED
INTERLOCKING RIDGE**
SCALE 1-1/2" = 1'

GENERAL NOTES:

1. THIS IS A PROTOTYPICAL DETAIL FOR REVIEW. MODIFICATIONS MAYBE REQUIRED TO MEET PROJECT SPECIFIC REQUIREMENTS.
2. MINIMUM 3/4" HEADLAP REQUIRED FOR ROUNDED INTERLOCKING RIDGE.
3. A BEAD OF SEALANT SHOULD BE APPLIED BETWEEN THE LAP OF EACH RIDGE TILE.



4757 Tile Plant Road, P.O. BOX 69, New Lexington, OH 43764
 Telephone: (888) 582-9052 Fax: (740) 342-1906
 www.ludowici.com

SYSTEM:	Greenwich Tile
Detail #:	GREENWICH-303
Description:	SECTION AT ROUNDED INTERLOCKING RIDGE
Drawing Date:	2014.10.11
Scale:	1-1/2" = 1'-0"
Ludowici N.A. Reference #:	Greenwich Tile GREENWICH-303

The information contained on this drawing is the sole property of Ludowici Roof Tile, Inc. Any reproduction in whole or part without the express written permission of Ludowici Roof Tile, Inc. is strictly prohibited. Ludowici Roof Tile, Inc. reserves the right to modify the configuration of item(s) shown without prior written notice when deemed necessary for product development and/or enhancement.